

# **SANDIA REPORT**

SAND2005-78817881

Unlimited Release

Printed November 2005

## **Interstitial Monitoring Technologies**

Michael J. Berg

Networked Systems Survivability & Assurance

and

Mark D. Torgerson

Cryptography and Information Systems Surety

Prepared by

Sandia National Laboratories

Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy's National Nuclear Security Administration under Contract DE-AC04-94AL85000.

Approved for public release; further dissemination unlimited.



**Sandia National Laboratories**

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

**NOTICE:** This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from  
U.S. Department of Energy  
Office of Scientific and Technical Information  
P.O. Box 62  
Oak Ridge, TN 37831

Telephone: (865) 576-8401  
Facsimile: (865) 576-5728  
E-Mail: [reports@adonis.osti.gov](mailto:reports@adonis.osti.gov)  
Online ordering: <http://www.osti.gov/bridge>

Available to the public from  
U.S. Department of Commerce  
National Technical Information Service  
5285 Port Royal Rd.  
Springfield, VA 22161

Telephone: (800) 553-6847  
Facsimile: (703) 605-6900  
E-Mail: [orders@ntis.fedworld.gov](mailto:orders@ntis.fedworld.gov)  
Online order: <http://www.ntis.gov/help/ordermethods.asp?loc=7-4-0#online>



# Interstitial Monitoring Technologies

Michael J. Berg  
Networked Systems Survivability & Assurance

and

Mark D. Torgerson  
Cryptography and Information Systems Surety

## **ABSTRACT**

When developing new hardware for a computer system, bus monitors are invaluable for testing compliance and troubleshooting problems. Bus monitors can be purchased for other common system busses such as the Peripheral Component Interconnect (PCI) bus and the Universal Serial Bus (USB). However, the project team did not find any commercial bus analyzers for the Low Pin Count (LPC) bus. This report will provide a short overview of the LPC interface.

This page intentionally left blank.

## TABLE OF CONTENTS

Abstract.....	3
Table of Contents.....	5
Introduction.....	7
The Low Pin Count (LPC) Interface .....	7
LPC Required Signal Descriptions .....	7
LAD[3:0] .....	7
LFRAME# .....	7
LRESET#.....	7
LCLK.....	7
Symbols .....	7
START.....	8
CYCTYPE_DIR .....	8
ADDR .....	8
IO_ADDR.....	8
IDSEL .....	8
MADDR .....	8
CHANNEL .....	8
SIZE.....	8
MSIZE .....	8
DATA .....	9
TAR (Turn-Around) .....	9
SYNC.....	9
Cycle Types .....	9
Memory Read/Write .....	9
I/O Read/Write.....	9
DMA Read/Write.....	10
Firmware Memory Read/Write.....	10
Bus Master Memory Read/Write.....	10
Bus Master I/O Read/Write .....	10
Conclusion .....	10
References.....	10
Distribution List.....	11

This page intentionally left blank.

## INTRODUCTION

When developing new hardware for a computer system, bus monitors are invaluable for testing compliance and troubleshooting problems. Bus monitors can be purchased for other common system busses such as the Peripheral Component Interconnect (PCI) bus and the Universal Serial Bus (USB). However, the project team did not find any commercial bus analyzers for the Low Pin Count (LPC) bus. This report will provide a short overview of the LPC interface, as specified in [1].

## THE LOW PIN COUNT (LPC) INTERFACE

This portion of the report is intended as an overview of the LPC interface as defined in [1]. The electrical domain details will be left to the full specification [1]. In addition, the specific bit patterns defined for each symbol will not be listed unless there is a reason to do so.

Signals with a # following their name are “active low” signals.

The LPC interface includes both required and optional signals. The required signals must be implemented by all LPC hosts and peripherals. Optional signals might not be implemented on many hosts or peripherals. This effort focused only on the required signals of the LPC interface.

The LPC required signals are

- LAD[3:0]
- LFRAME#
- LRESET#
- LCLK

## LPC Required Signal Descriptions

### *LAD[3:0]*

This bidirectional, four bit bus carries the address, data, and other information transmitted between the host and peripherals on the LPC bus during the course of an LPC bus cycle.

### *LFRAME#*

LFRAME# is used by the host to signal the start of a new LPC cycle to all the peripherals on the LPC bus. LFRAME# is also used to terminate broken cycles.

### *LRESET#*

LRESET# is the reset signal for the LPC host and peripherals. LRESET# is the same as the PCI reset signal.

### *LCLK*

LCLK is the 33 MHz clock from the PCI bus.

## Symbols

During an LPC bus cycle, the values on LAD[3:0] take on different meanings in the protocol. Each of these meaning is given a symbolic name.

## ***START***

There are three categories of LPC cycles

- Memory, I/O, and DMA
- Firmware
- Bus Mastered Memory and I/O

The start of an LPC cycle is identified by the LFRAME# signal being asserted (going low). The value on LAD[3:0] when LFRAME# is negated (goes high) is used as the START field. The value of the START field determines which of the three categories the LPC cycle is going to be.

## ***CYCTYPE\_DIR***

For memory, I/O, and DMA cycles, the CYCTYPE\_DIR field is the value on LAD[3:0] during the single clock cycle following the START field. This field distinguishes the type of the cycle (memory, I/O, or DMA) and the direction of the cycle (a read or a write).

## ***ADDR***

The ADDR field occupies eight clock cycles and is composed of a 32 bit memory address that is transferred most significant nibble first across LAD[3:0]. The ADDR field is used during memory cycles.

## ***IO\_ADDR***

The IO\_ADDR field occupies four clock cycles and is composed of a 16 bit I/O address that is transferred most significant nibble first across LAD[3:0]. The IO\_ADDR field is used during I/O cycles.

## ***IDSEL***

The IDSEL field occupies one clock cycle and indicates which firmware device is being selected during firmware access cycles.

## ***MADDR***

The MADDR field occupies seven clock cycles and is composed of a 28 bit address that is transferred most significant nibble first across LAD[3:0]. MADDR is used during firmware access cycles. Together, IDSEL and MADDR can alternately be viewed as a 32 bit address.

## ***CHANNEL***

The CHANNEL field occupies one clock cycle during a DMA cycle and notifies the peripherals which DMA channel has been granted.

## ***SIZE***

The SIZE field occupies one clock cycle and indicates how many bytes of data will be transferred during the DMA cycle.

## ***MSIZE***

The MSIZE field occupies one clock cycle and indicates how many bytes of data will be transferred during the firmware access cycle.



## DATA

Each DATA field occupies two clock cycles and is composed of a single byte of data that is transferred least significant nibble first across LAD[3:0].

## TAR (Turn-Around)

The TAR field occupies two clock cycles. During the first clock cycle, the device currently driving the bus will drive LAD[3:0] to b"1111". During the second clock cycle, the driving device will stop driving the bus so that the other device it is communicating with can begin driving the bus. Weak pull-up resistors on the bus keep LAD[3:0] at b"1111" during the second clock cycle.

## SYNC

The SYNC field occupies at least once clock cycle to indicate that synchronization was achieved without error, and may occupy additional clock cycles to insert wait states if needed. There are two types of wait states: short waits and long waits. Short waits can last a maximum of eight clock cycles. Long waits do not have a defined maximum number of clock cycles.

## Cycle Types

This section describes the sequences of symbols that constitute the valid LPC bus cycles. Symbols or sequences of symbols that can occur multiple times during an LPC cycle are followed by a set containing the number of times that they can occur. For example, if the DATA symbol can occur consecutively one, two, or four times, it will be written as DATA{1,2,4}. Similarly, the sequence (SYNC + DATA){1,2} would indicate that either of "SYNC + DATA" or "SYNC + DATA + SYNC + DATA" are valid sequences that could occur at that position.

To keep each cycle type readable, a preamble is defined for each cycle type that includes the START symbol and any address and size symbols. Both the read and write variants of each cycle type begin with the same preamble.

During normal cycles, the host controls the preamble. During bus master cycles, the host drives a START code to identify it as a bus master cycle, and then turns control of the bus over to a peripheral that drives the rest of the preamble to identify the cycle type, direction, address, and size.

BLUE\_NORMAL = Host drives the bus. RED\_ITALIC = Peripheral drives the bus.

## Memory Read/Write

Read sizes supported: 1 byte

Write sizes supported: 1 byte

```
MEM_PREAMBLE := START + CYCTYPE_DIR + ADDR
MEM_R := MEM_PREAMBLE + TAR + SYNC + DATA + TAR
MEM_W := MEM_PREAMBLE + DATA + TAR + SYNC + TAR
```

## I/O Read/Write

Read sizes supported: 1 byte

Write sizes supported: 1 byte

```
IO_PREAMBLE := START + CYCTYPE_DIR + IO_ADDR
IO_R := IO_PREAMBLE + TAR + SYNC + DATA + TAR
IO_W := IO_PREAMBLE + DATA + TAR + SYNC + TAR
```

### ***DMA Read/Write***

Read sizes supported: 1, 2, 4 bytes

Write sizes supported: 1, 2, 4 bytes

```
DMA_PREAMBLE := START + CYCTYPE_DIR + CHANNEL + SIZE
DMA_R := DMA_PREAMBLE + (DATA + TAR + SYNC + TAR){1,2,4}
DMA_W := DMA_PREAMBLE + TAR + (SYNC + DATA){1,2,4} + TAR
```

### ***Firmware Memory Read/Write***

Read sizes supported: 1, 2, 4, 16, 128 bytes

Write sizes supported: 1, 2, 4 bytes

```
FIRMWARE_PREAMBLE := START + IDSEL + MADDR + MSIZE
FIRMWARE_R := FIRMWARE_PREAMBLE + TAR + SYNC + DATA{1,2,4,16,128} + TAR
FIRMWARE_W := FIRMWARE_PREAMBLE + DATA{1,2,4} + TAR + SYNC + TAR
```

### ***Bus Master Memory Read/Write***

Read sizes supported: 1, 2, 4 bytes

Write sizes supported: 1, 2, 4 bytes

```
BM_MEM_PREAMBLE := START + TAR + CYCTYPE_DIR + ADDR + SIZE
BM_MEM_R := BM_MEM_PREAMBLE + TAR + SYNC + DATA{1,2,4} + TAR
BM_MEM_W := BM_MEM_PREAMBLE + DATA{1,2,4} + TAR + SYNC + TAR
```

### ***Bus Master I/O Read/Write***

Read sizes supported: 1, 2, 4 bytes

Write sizes supported: 1, 2, 4 bytes

```
BM_IO_PREAMBLE := START + TAR + CYCTYPE_DIR + IO_ADDR + SIZE
BM_IO_R := BM_IO_PREAMBLE + TAR + SYNC + DATA{1,2,4} + TAR
BM_IO_W := BM_IO_PREAMBLE + DATA{1,2,4} + TAR + SYNC + TAR
```

## **CONCLUSION**

This report provided a high level overview of the Low Pin Count (LPC) interface.

## **REFERENCES**

[1] Intel® Low Pin Count (LPC) Interface Specification, August 2002, Revision 1.1:  
<http://www.intel.com/design/chipsets/industry/25128901.pdf>

## **DISTRIBUTION LIST**

2	MS0672	M. J. Berg, 5616
1	MS0672	R. L. Hutchinson, 5616
1	MS0672	T. S McDonald, 5614
2	MS0672	M. D. Torgerson, 5614
1	MS0671	R. E. Trellue, 5610
1	MS0455	S. G. Varnado, 5600
1	MS9018	Central Technical Files, 8945-1
2	MS0899	Technical Library, 9616
2	MS0612	Review & Approval Desk 9612 For DOE/OSTI
1	MS0123	LDRD Program Office Attn: Donna Chavez